

GCL1800

## 17" LCD KVM Combo Console (TAA Compliant)

- Integrated KVM console featuring a 17" TFT LCD active matrix monitor, keyboard and touchpad
- 1280 x 1024 resolution on 19" rack mount LCD provides a sharp video display
- USB or PS/2 keyboard and mouse
- Built-in USB 1.1 port for external mouse
- Adjustable depth to fit different sizes of racks



- Integrated KVM console featuring a 17" TFT LCD active matrix monitor, keyboard and touchpad
- 1280 x 1024 resolution on 19" rack mount LCD provides a sharp video display
- USB or PS/2 keyboard and mouse
- Built-in USB 1.1 port for external mouse
- Adjustable depth to fit different sizes of racks
- Multi platform OS support - Windows®, Mac, Sun Solaris™, and Linux®

- Easy to operate - intuitive LCD OSD (on screen display) and hotkeys
- Support special keys on Mac and Sun keyboards
- Rack mountable in a 19" (1U) system rack
- Custom ASIC provides an auto-sensing function that recognizes the position of each station on the installation
- Firmware upgradeable
- Fully Supports DDC2B
- TAA Compliant



## Requirements

### Computers:

- VGA, SVGA, or MultiSync video graphics card with an HDB-15 port
- PS/2 mouse and keyboard ports (6-pin mini DIN) or 1 USB port

## Package Contents

- 1 x 17" LCD Console
- 1 x USB KVM Cable
- 1 x Firmware Upgrade Cable
- 2 x Rack Mount Kit - Short Bracket( Fits 16.6~28.3 Inch Depth) and Long Brackets(Fits 26.8~39.3 Inch Depth)
- 1 x Grounding Wire
- 1 x Power Cord
- 1 x Installation Guide
- 1 x Warranty Card

## Specifications

Function	GCL1800
<b>Computer Connections</b>	
Direct	1
Daisy Chain or Cascading	256 (If cascaded with GCS1716s)
<b>Connectors</b>	
Second Console Video	1 x HDB-15 Female
Second Console Keyboard	PS/2 or USB
Second Console Mouse	PS/2 or USB
Mouse	1 x USB (External USB Mouse Port)
Power	1 x 3-Prong AC Socket
<b>Console Connectors</b>	
Flash ROM Upgrade	1 x RJ-11 Female
<b>CPU Connectors</b>	
Keyboard, Mouse, and Monitor	1 x SPHD-15 Female
<b>Switches</b>	
Power	1 x Rocker Switch
Reset	1 x Semi-recessed Pushbutton
F/W Upgrade	1 x Switch
LCD Power	1 x LED Pushbutton (Orange)
LCD Adjustment	4 x Pushbutton
<b>LEDs</b>	
Power On	Dark Green
<b>Emulation</b>	
Keyboard	PS/2, USB
Mouse	PS/2, USB
<b>Video Resolution</b>	1280 x 1024 @ 75Hz; DDC2B
<b>Power Input Rating</b>	
Per AC Power Inlet, 50/60Hz	100~240VAC, 50/60Hz, 1A
<b>Power Consumption</b>	120V, 29.6W
<b>Environment</b>	
Operation Temperature	0~40°C
Storage Temperature	-20~60°C
Humidity	0~80% RH; Non-condensing
<b>Housing</b>	
Case	Metal and Plastic

Dimensions	GCL1800
<b>Unit Dimensions</b>	
Height	1.75in.
Depth	21in.
Width	19in.
<b>Unit Package Dimensions</b>	
Height	5.5in.
Width	26.75in.
Depth	28.5in.
<b>Master Carton</b>	
Master Carton Qty.	1
<b>Weight</b>	
Unit Pack Wt.	40.1lb
Unit Wt. w/accessories	30.27lb
Unit Wt.	25.94lb