

GCL1800

17" LCD KVM Combo Console (TAA Compliant)

- Integrated KVM console featuring a 17" TFT LCD active matrix monitor, keyboard and touchpad
- 1280 x 1024 resolution on 19" rack mount LCD provides a sharp video display
- USB or PS/2 keyboard and mouse
- Built-in USB 1.1 port for external mouse
- Adjustable depth to fit different sizes of racks



- Integrated KVM console featuring a 17" TFT LCD active matrix monitor, keyboard and touchpad
- 1280 x 1024 resolution on 19" rack mount LCD provides a sharp video display
- USB or PS/2 keyboard and mouse
- Built-in USB 1.1 port for external mouse
- Adjustable depth to fit different sizes of racks
- Multi platform OS support - Windows®, Mac, Sun Solaris™, and Linux®

- Easy to operate - intuitive LCD OSD (on screen display) and hotkeys
- Support special keys on Mac and Sun keyboards
- Rack mountable in a 19" (1U) system rack
- Custom ASIC provides an auto-sensing function that recognizes the position of each station on the installation
- Firmware upgradeable
- Fully Supports DDC2B
- TAA Compliant



Requirements

Computers:

- VGA, SVGA, or MultiSync video graphics card with an HDB-15 port
- PS/2 mouse and keyboard ports (6-pin mini DIN) or 1 USB port

Package Contents

- 1 x 17" LCD Console
- 1 x USB KVM Cable
- 1 x Firmware Upgrade Cable
- 2 x Rack Mount Kit - Short Bracket(Fits 16.6~28.3 Inch Depth) and Long Brackets(Fits 26.8~39.3 Inch Depth)
- 1 x Grounding Wire
- 1 x Power Cord
- 1 x Installation Guide
- 1 x Warranty Card

Specifications

| Function | GCL1800 |
|------------------------------|-----------------------------------|
| Computer Connections | |
| Direct | 1 |
| Daisy Chain or Cascading | 256 (If cascaded with GCS1716s) |
| Connectors | |
| Second Console Video | 1 x HDB-15 Female |
| Second Console Keyboard | PS/2 or USB |
| Second Console Mouse | PS/2 or USB |
| Mouse | 1 x USB (External USB Mouse Port) |
| Power | 1 x 3-Prong AC Socket |
| Console Connectors | |
| Flash ROM Upgrade | 1 x RJ-11 Female |
| CPU Connectors | |
| Keyboard, Mouse, and Monitor | 1 x SPHD-15 Female |
| Switches | |
| Power | 1 x Rocker Switch |
| Reset | 1 x Semi-recessed Pushbutton |
| F/W Upgrade | 1 x Switch |
| LCD Power | 1 x LED Pushbutton (Orange) |
| LCD Adjustment | 4 x Pushbutton |
| LEDs | |
| Power On | Dark Green |
| Emulation | |
| Keyboard | PS/2, USB |
| Mouse | PS/2, USB |
| Video Resolution | 1280 x 1024 @ 75Hz; DDC2B |
| Power Input Rating | |
| Per AC Power Inlet, 50/60Hz | 100~240VAC, 50/60Hz, 1A |
| Power Consumption | 120V, 29.6W |
| Environment | |
| Operation Temperature | 0~40°C |
| Storage Temperature | -20~60°C |
| Humidity | 0~80% RH; Non-condensing |
| Housing | |
| Case | Metal and Plastic |

| Dimensions | GCL1800 |
|--------------------------------|----------|
| Unit Dimensions | |
| Height | 1.75in. |
| Depth | 21in. |
| Width | 19in. |
| Unit Package Dimensions | |
| Height | 5.5in. |
| Width | 26.75in. |
| Depth | 28.5in. |
| Master Carton | |
| Master Carton Qty. | 1 |
| Weight | |
| Unit Pack Wt. | 40.1lb |
| Unit Wt. w/accessories | 30.27lb |
| Unit Wt. | 25.94lb |