

GCS1414TAA4

# 4-Port Single View DisplayPort Secure KVM Switch w/Audio



- NIAP-Certified PP4.0
- 4-Port Single View DisplayPort Secure KVM Switch
- Superior 4K UHD Video Resolution
- PP4.0 Certified Remote Port Selector\*\* Support


## 4-Port Single View DisplayPort Secure KVM with Audio Protection Profile v4.0

Secure and manage multiple data-sensitive systems from one workstation from internal and external cybersecurity threats with the TAA-compliant IOGEAR 4-Port Single View DisplayPort Secure KVM with Audio Protection Profile v4.0. Enable authorized users secure access to up to four systems with one keyboard, mouse, a 4K @30Hz monitor.

Featuring the latest in Common Criteria and NIAP Protection Profile v4.0 security requirements set for the U.S. government for peripheral sharing switches, the secure KVM switches are built for multiple interfaces and ideal for use in high-security environments that demand rigorous cybersecurity provisions including military and defense, federal agencies, government, utilities, commercial and healthcare applications.

- NIAP-Certified PP4.0  
Validated to Protection Profile for Peripheral Sharing Device v4.0
  - 4-Port Single View DisplayPort Secure KVM Switch  
One USB console controls 4 secure computers on 1 display
  - Superior 4K UHD Video Resolution  
  
UHD Resolution: 3840 x 2160 @30Hz
  - Port Selection via Push-Button and Remote Port Selector\*\* for Enhanced Security  
Keyboard restrictions - OSD & hotkey methods are not allowed
  - Isolated Channel per Port  
Unidirectional data flow restricts data leakage between connected computers
  - Active Chassis Intrusion Detection  
Compromising the unit's cover renders the switch inoperable
  - Tamper-Evident Seals  
Visually detect attempts to gain access to switch's internal components
  - Tamper-Proof Hardware  
Integrated circuits are soldered directly onto the circuit board to hinder component sabotage
  - Non-Reprogrammable Firmware  
Prevents tampering and attempts to reprogram the switch's firmware
  - Clears Keyboard Buffer  
Data clears automatically after transmission to switch and resets
  - Analog Speaker Support
  - Secure audio data input does not convert digital audio to analog audio
  - Multiplatform Support  
Windows® 2000, Vista, 7, 8, 8.1, 10, 11 Linux, Mac OS X, & Sun
  - Rugged Metal Enclosure  
Durable, Full Metal Chassis
  - Build-In, Internal Power Supply
- \*\* Remote Port Selector sold separately





### Requirements

### Package Contents

#### Console

- DisplayPort monitor capable of the highest resolution that you will be using on any computer in the installation
- Standard 104-key wired USB keyboard
- Standard 2 or 3 button wired USB mouse
- Speaker (optional)

- 1x 4-Port Single View DP Secure KVM
- 1x Power Cord
- 1x User Guide
- 1x Warranty Card

#### Computers

- 1 x DisplayPort Video output connector
- A USB Type A port for keyboard and mouse
- A 3.5mm jack Audio port for speaker (Optional)

#### Operating Systems

- Win 7, 8, 10, 11
- Linux: Kernel2.6+, RedHat v6.0+, SuSE v8.2+ Mandriva(Mandrake) v9.0+
- Unix: AIX v4.3, FreeBSD v3.51+, Sun Solaris v9.0+
- Novell Netware v5.0+Mac OS v9+
- DOS v6.2+

## Specifications

Function	GCS1414TAA4	Dimensions	GCS1414TAA4
<b>Computer Connections</b>		<b>Unit Package Dimensions</b>	
Direct	4	Height	4.75 in. (12 cm)
<b>Port Selection</b>		Length	16.5 in. (41.9 cm)
	Pushbutton or Remote Port Selector	Width	8.25 in. (21 cm)
<b>Console Connectors</b>		<b>Master Carton</b>	
Monitor	1 x DisplayPort Female (Black)	Height	9.25 in. (23.5 cm)
Keyboard	1 x USB Type-A Female (Black)	Length	15 in. (38.1 cm)
Mouse	1 x USB Type-A Female (Black)	Width	17 in. (43.2 cm)
Audio	1 x Mini Stereo 3.5mm Jack Female (Green)	Master Carton Qty.	3
<b>CPU Connectors</b>		<b>Weight</b>	
Monitor	4 x DisplayPort Female (Black)	Master Carton Wt.	16.95 lb. (7.7 kg)
Keyboard & Mouse	4 x USB Type-B Female (White)	Unit Pack Wt.	5.15 lb. (2.3 kg)
Audio	4 x Mini Stereo 3.5mm Jack Female (Green)		
<b>Switches</b>			
Port Selection	4 x Pushbuttons		
Power	1 x Rocker		
Reset	1 x Semi-recessed Pushbutton		
<b>LEDs</b>			
On Line	4 x Orange		
Selected	4 x Orange		
Power On	1 x Green		
Key Lock	3 x Green (Num Lock, Caps Lock, Scroll Lock)		
Console Video	1 x Green (Rear Panel)		
<b>Remote Port Selector</b>	1x RJ-11		
<b>Emulation</b>			
Keyboard	USB		
Mouse	USB		
<b>Video Resolution</b>	Up to 3840 x 2160 @ 30Hz (UHD)		
<b>Power</b>			
Input Rating	100 ~240V, 50 ~ 60 Hz; 1A		
<b>Environment</b>			
Operation Temperature	0 - 50C		
Storage Temperature	-20 - 60C		
Humidity	0 - 80% RH, Non-condensing		
<b>Housing</b>			
Case	Metal		