

GCS1424TAA4-UN

# Universal 4-Port Dual View DisplayPort/HDMI Secure KVM Switch Kit w/Audio



- NIAP-CERTIFIED PP v4.0: Certified to Protection Profile v4.0 security requirements
- 4-Port Dual View DisplayPort Secure KVM Switch: One USB console controls 4 secure computers with two 4K displays
- Support DisplayPort and HDMI video Interfaces
- PP4.0 Certified Remote Port Selector\*\* Support

## 4-Port Dual View DisplayPort/HDMI Universal Secure KVM Switch Kit w/Audio

Secure and manage multiple data-sensitive systems from one workstation from internal and external cybersecurity threats with the TAA-compliant IOGEAR 4-Port Dual View DisplayPort/HDMI Universal Secure KVM Switch Kit w/Audio . Enable authorized users secure access to up to four systems with one keyboard, mouse, up to two 4K @30Hz monitors.

Featuring the latest in Common Criteria and NIAP Protection Profile v4.0 security requirements set for the U.S. government for peripheral sharing switches, the secure KVM switches are built for multiple interfaces and ideal for use in high-security environments that demand rigorous cybersecurity provisions including military and defense, federal agencies, government, utilities, commercial and healthcare applications.

- NIAP-Certified PP4.0  
Validated to Protection Profile for Peripheral Sharing Device v4.0
- 4-Port Dual View DisplayPort/HDMI Secure KVM Switch  
One USB console controls 4 secure computers on 2 displays
- Superior 4K UHD Video Resolution

UHD Resolution: 3840 x 2160 @30Hz

- Multiple Video Interface Support

Support DisplayPort and HDMI video interfaces

- Port Selection via Push-Button and Remote Port Selector\*\* for Enhanced Security  
Keyboard restrictions - OSD & hotkey methods are not allowed
- Isolated Channel per Port  
Unidirectional data flow restricts data leakage between connected computers
- Active Chassis Intrusion Detection  
Compromising the unit's cover renders the switch inoperable

- Tamper-Evident Seals  
Visually detect attempts to gain access to switch's internal components
- Tamper-Proof Hardware  
Integrated circuits are soldered directly onto the circuit board to hinder component sabotage
- Non-Reprogrammable Firmware  
Prevents tampering and attempts to reprogram the switch's firmware
- Clears Keyboard Buffer  
Data clears automatically after transmission to switch and resets
- Analog Speaker Support
- Secure audio data input does not convert digital audio to analog audio
- Multiplatform Support  
Windows® 2000, Vista, 7, 8, 8.1, 10, 11 Linux, Mac OS X, & Sun
- Rugged Metal Enclosure  
Durable, Full Metal Chassis
- Build-In, Internal Power Supply

\*\* Remote Port Selector sold separately





## Specifications

Function	GCS1424TAA4-UN
<b>Computer Connections</b>	
Direct	4
<b>Port Selection</b>	
	Pushbutton or Remote Port Selector
<b>Console Connectors</b>	
Monitor	2 x DisplayPort Female (Black)
Keyboard	1 x USB Type-A Female (Black)
Mouse	1 x USB Type-A Female (Black)
Audio	1 x Mini Stereo 3.5mm Jack Female (Green)
<b>CPU Connectors</b>	
Monitor	8 x DisplayPort Female (Black)
Keyboard & Mouse	4 x USB Type-B Female (White)
Audio	4 x Mini Stereo 3.5mm Jack Female (Green)
<b>Switches</b>	
Port Selection	4 x Pushbuttons
Power	1 x Rocker
<b>LEDs</b>	
On Line	4 x Orange
Selected	4 x Orange
Power On	1 x Green
Key Lock	3 x Green (Num Lock, Caps Lock, Scroll Lock)
Console Video	2 x Green (Rear Panel)
<b>Emulation</b>	
Keyboard	USB
Mouse	USB
<b>Video Resolution</b>	
	Up to 3840 x 2160 @ 30Hz (UHD)
<b>Power</b>	
Input Rating	100 ~240V, 50 ~ 60 Hz, 1A
<b>Environment</b>	
Operation Temperature	0 - 50C
Storage Temperature	-20 - 60C
Humidity	0 - 80% RH, Non-condensing
<b>Housing</b>	
Case	Matel

Dimensions	GCS1424TAA4-UN
<b>Unit Package Dimensions</b>	
Height	9 in. (22.9 cm)
Length	22 in. (55.9 cm)
Width	10 in. (25.4 cm)
<b>Master Carton</b>	
Height	9 in (22.9 cm)
Length	22 in. (55.9 cm)
Width	10 in. (25.4 cm)
Master Carton Qty.	1
<b>Weight</b>	
Master Carton Wt.	14.65 lb. (6.6kg)
Unit Pack Wt.	14.65 lb. (6.66 kg)