

GCS1734

4-Port MiniView™ Extreme Multimedia KVMP Switch w/Cables

- Control four USB or PS/2* computers from 1 keyboard, monitor, and mouse
- Share two USB peripheral devices such as printers and scanners, as well as speakers and a microphone*
- High Resolution: Up to 2048 x 1536
- Multi OS platform support
- · Computer switching via front panel pushbuttons or hotkeys



4-Port VGA KVMP Switch with USB & PS/2 Interface and Audio

IOGEAR's MiniView™ Extreme Multimedia KVM and Peripheral Sharing Switch brings extra value to conventional KVM switches by offering USB peripheral sharing capabilities, audio and microphone support. Control and switch up to 4 computers from a set of USB or PS/2 keyboard, mouse, and VGA monitor. This 4-Port VGA KVMP switch is an out-of-the-box solution as all cables* are included. Save money and reduce clutter by eliminating the need for multiple monitors, keyboards, mice, and peripheral devices such as printers, scanners, external hard drives, and more. Up to 127 different USB devices can be daisy chained from this KVMP switch. Sharing speakers and a microphone also offers extra value and convenience for the users.

USB and KVM technology together makes cross-platform management easy. A single USB console can control a PC and a Mac, or even a Sun workstation, and share peripherals and audio devices between the computers. Any USB-enabled computers, using any USB-compatible operating system, can benefit from the efficiency, expense reduction and convenience of IOGEAR's MiniView™ Extreme KVMP switch.

*In the case when you need extra cables for PS/2 connections: IOGEAR Part No. G2L5302P

- Control four USB or PS/2* computers from 1 keyboard, monitor, and mouse
- Share two USB peripheral devices such as printers and scanners, as well as speakers and a microphone*
- High Resolution: Up to 2048 x 1536
- · Multi OS platform support
- · Computer switching via front panel pushbuttons or hotkeys
- Asynchronous hotkey switching between KVM focus, USB peripheral, and Audio ports
- Complete keyboard and mouse emulation for error free booting
- · Support special keys on Mac and Sun keyboard
- · LED display for easy status monitoring
- Easy installation: no software required, hot swappable
- Firmware Upgradable

*PS/2 KVM Cables are available and sold separately.









Requirements

• Console:

1x VGA Display

1 x standard 104 key wired USB keyboard

1 x standard wired USB mouse

• Computers:

VGA Port USB Port* Audio / Mic Port

• Operating Systems:

Windows® XP, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10 Mac OS 9 to 10.x Oracle® Solaris
Linux®, Unix and other USB supported systems*

Package Contents

- 1 MiniView™ Extreme Multimedia KVMP switch
- 4 USB KVM bonded cables
- 1 User manual
- 1 Warranty card
- 1 Power adapter
- 1 Firmware upgrade cable

^{*}Additional drivers and support may be needed.

^{**}PS/2 KVM Cables are available and sold separately.

^{***}Does not support display emulation for Windows 7 (EDID).



Specifications

Function	GCS1734
Housing	
Case	Plastic/Metal
Console Connectors	
Mouse	1 x USB Type A
Keyboard	1 x USB Type A
Monitor	1 x HDB-15 Female (Std. VGA/SVGA)
Audio	1 x stereo speaker; 1 x Microphone
Flash ROM Upgrade	1 x RJ11 socket
Power	
Voltage	DC 5V
Amps	2.6 AMP
LEDs	
Selected	4
On Line	4
USB Peripherals	4
Port Selection	Push button, Hot Keys
Power Consumption	Bus powered, power adapter for additional power
Video Resolution	2048x1536 (Max.); DDC/ DDC2B/ DDC2AB
Scan Interval	5 sec.
Emulation	
Keyboard	USB Plug-n-Play
Mouse	USB Plug-n-Play
Computer Connections	
Direct	4
Direct CPU Connectors	4
	4 4 x stereo speaker; 4 x Microphone
CPU Connectors	
CPU Connectors Audio	4 x stereo speaker; 4 x Microphone
CPU Connectors Audio Peripherals	4 x stereo speaker; 4 x Microphone 2 x USB Type A
CPU Connectors Audio Peripherals Keyboard, Mouse, and Monitor	4 x stereo speaker; 4 x Microphone 2 x USB Type A 4 x SPDB15
CPU Connectors Audio Peripherals Keyboard, Mouse, and Monitor Operating Temperature	4 x stereo speaker; 4 x Microphone 2 x USB Type A 4 x SPDB15 4 - 40 C
CPU Connectors Audio Peripherals Keyboard, Mouse, and Monitor Operating Temperature Storage Temperature	4 x stereo speaker; 4 x Microphone 2 x USB Type A 4 x SPDB15 4 - 40 C -20 - 60 C
CPU Connectors Audio Peripherals Keyboard, Mouse, and Monitor Operating Temperature Storage Temperature Humidity	4 x stereo speaker; 4 x Microphone 2 x USB Type A 4 x SPDB15 4 - 40 C -20 - 60 C 0 - 80% RH
CPU Connectors Audio Peripherals Keyboard, Mouse, and Monitor Operating Temperature Storage Temperature Humidity Cable Length	4 x stereo speaker; 4 x Microphone 2 x USB Type A 4 x SPDB15 4 - 40 C -20 - 60 C 0 - 80% RH 4 ea 6 ft (1.8M)
CPU Connectors Audio Peripherals Keyboard, Mouse, and Monitor Operating Temperature Storage Temperature Humidity Cable Length Peripheral Sharing	4 x stereo speaker; 4 x Microphone 2 x USB Type A 4 x SPDB15 4 - 40 C -20 - 60 C 0 - 80% RH 4 ea 6 ft (1.8M)
CPU Connectors Audio Peripherals Keyboard, Mouse, and Monitor Operating Temperature Storage Temperature Humidity Cable Length Peripheral Sharing Power Adaptor Part #	4 x stereo speaker; 4 x Microphone 2 x USB Type A 4 x SPDB15 4 - 40 C -20 - 60 C 0 - 80% RH 4 ea 6 ft (1.8M) USB, selected through Hotkeys

Dimensions	GCS1734
Unit Dimensions	
Height	1.7 in. (4.318 cm.)
Depth	3.5 in. (8.89 cm.)
Width	8 in. (20.32 cm.)
Inner Pack	
Height	13.625 in.(34.59cm)
Length	9.125 in. (23.17cm)
Width	14.75 in. (37.465 cm)
Inner Pack Qty.	3
Unit Package Dimensions	
Height	8.3 in. (21 cm)
Width	3.8 in. (9.7 cm)
Depth	12.8 in. (32.5 cm)
Master Carton	
Height	13.8 in. (35 cm)
Width	17.7 in. (45 cm)
Depth	12.6 in. (32 cm)
Master Carton Qty.	6
Weight	
Master Carton Wt.	29.5 lb. (13.4 kg)
Inner Pack Wt.	15.35 lb. (6.962 kg)
Unit Pack Wt.	4.7 lb. (2.131 kg)
Unit Wt.	1.1 Lbs. (0.50 kg.)