

GCS62DP

2-Port DisplayPort KVM

- Share Cinema 4K DisplayPort monitors (4096 x 2160 @60Hz)
- Operate 2 DisplayPort computers with 1 keyboard, mouse, and 1 monitor
- Switching via pushbutton, hotkeys, or mouse
- Save Cabling Costs: ALL cables are included
- Added features via firmware updates



DisplayPort KVM [2-Port]

IOGEAR's 2-Port DisplayPort KVM switch with audio and DisplayPort 1.2 connections break revolutionary new ground in KVM functionality by combining advanced Cinema 4K Video and USB 2.0 technology. It enables effortless control over two 4K-enabled computers with DisplayPort video connections using a single USB keyboard, USB mouse and DisplayPort video console.

- Control 2 computers using a single keyboard, mouse, and DisplayPort video console
- DisplayPort 1.2 Compliant, HDCP Compliant
- Computer selection via console selection button, hotkeys, and USB mouse¹
- Superior video quality – up to 4K Cinema (4096 x 2160 @ 60Hz)
- Multiplatform support – Windows®, Mac OS®, Linux®
- Compatible with widescreen LCD monitors
- Power-on detection – if either of the connected computers is powered off, the GCS62DP will automatically switch to the other computer
- Independent switching of the KVM, USB, and 2.1 channel audio focus
- Supports 7.1 HD audio through DisplayPort playback²
- Supports multimedia keyboards, wireless keyboards and mice
- Console mouse port emulation/bypass feature supports most mouse drivers and multifunction mice
- Mac keyboard support and emulation
- USB 2.0 mouse port can be used for USB hubs and USB peripheral sharing³
- Bus-Powered
- Firmware upgradable
- All cables included

[1] Mouse port switching is only supported under mouse emulation mode and by USB 3-key wheel mice.

[2] HD audio through DisplayPort cannot be switched independently.

[3] This feature may require an extra power adapter to be connected to the USB hub and that the GCS62DP's Mouse Emulation Mode be disabled



How does it work?



Requirements

Package Contents

- | | |
|---|---|
| <ul style="list-style-type: none"> • Console • DisplayPort compatible monitor • Standard 104 key wired USB keyboard • Standard 2 or 3 button wired USB mouse • Microphone and speakers (optional) <ul style="list-style-type: none"> • Computer • DisplayPort port • Type A USB port • Audio ports (optional) <ul style="list-style-type: none"> • Operating System • Windows® 7, Windows® 8.1, Windows® 10 • Mac OS® X 10.7 + | <ul style="list-style-type: none"> • 1 x GCS62DP • 2 x DisplayPort Cable (6ft.) • 2 x USB 2.0 A to B Cable (6ft.) • 2 x 3.5mm Audio Cable (6ft.) • 1 x Port Selection Remote • 1 x Quick Start Guide • 1 x Warranty Card |
|---|---|

*Use with video adapter may change performance

Specifications

| Function | GCS62DP | Dimensions | GCS62DP |
|-----------------------------|--|--------------------------------|-------------------|
| Computer Connections | | POP Information | |
| Direct | 2 | 10" Peg Hook | 3 |
| Port Selection | Hotkeys, Mouse, or Port Selection Remote | 6" Peg Hook | 2 |
| Console Connectors | | Unit Dimensions | |
| Monitor | DisplayPort 1.2 | Height | 1.06" (2.69cm) |
| Mouse | 1 x USB 2.0 Type A Female | Depth | 3.75" (9.53cm) |
| Keyboard | 1 x USB 2.0 Type A Female | Length | 3.75" (9.53cm) |
| Audio | 1 x 3.5mm Mini Stereo Jack Female | Unit Package Dimensions | |
| CPU Connectors | | Width | 6.43" (16.33cm) |
| Audio | 2 x 3.5mm Mini Stereo Jack Female | Height | 9.25" (23.5cm) |
| Monitor | 2 x DisplayPort 1.2 | Depth | 2.81" (7.13cm) |
| Keyboard & Mouse | 2 x USB 2.0 Type B Female | Master Carton | |
| Video Resolution | up to 4096 x 2160 @60Hz | Width | 16" (40.64cm) |
| | | Height | 7.375" (18.733cm) |
| | | Depth | 9.375" (23.813cm) |
| | | Master Carton Qty. | 6 |
| | | Weight | |
| | | Master Carton Wt. | 9.85lb (4.46kg) |
| | | Unit Pack Wt. | 1.5lb (0.7kg) |
| | | Unit Wt. | 0.25lb (0.12kg) |