

GCS632U

MiniView™ Micro USB PLUS KVM Switch with audio and cables



2-Port USB VGA Cable KVM Switch with Audio

Introducing IOGEAR's 2-Port MiniView™ Micro USB PLUS KVM switch – the simplest way to simultaneously control and switch between two computers from with a single USB keyboard, monitor and USB mouse. This self-powered KVM switch features the unique USB mouse and keyboard emulation to ensure smooth operation, as well as support for Plug-n-Play monitors and most wheel mice. With 6' long KVM cables molded into the MiniView Micro USB PLUS, all you need to do is to plug it into your computers and you've got a complete KVM solution from IOGEAR.

Video and Audio Support

Patented VSE Video Signal Enhancement® technology provides rich, 32-bit color at resolutions up to 2048 x 1536. Another big plus is this 2-Port VGA KVM's capability to provide audio support, allowing you to share your multimedia speakers among the two connected computers.

- Use one USB keyboard, monitor and USB mouse to control two USB computers
- Increase security for your intranet by separating a PC connected to the Internet and a PC connected to an Intranet
- 6' long molded-in cables to simplify setup
- Share your multimedia speakers among the two connected computers
- Full support for Mac and Sun systems
- Supports special keys on Mac and Sun keyboards
- Port selection through convenient Hot Keys
- USB sniffing technology allows complete USB mouse and keyboard emulation for error-free boot-up
- Plug-n-Play monitor support
- Support video resolutions up to 2048 x 1536
- No software required
- Built in AutoScan mode
- LEDs allow for easy status monitoring
- 3 Year Limited Warranty



Requirements

Console:

- 1 x VGA display
- 1 x standard 104 key wired USB keyboard
- 1 x standard 2 or 3 button wired USB mouse

Computers:

- 1 x VGA port
- 1 x USB ports
- 1 x 3.5mm audio port

Operating Systems:

- Windows® 7, 8.1, 10, 11
- Mac OS® X 9.0+
- Oracle® Solaris
- Linux®, Unix and other USB supported systems*

*Additional drivers and support may be needed

**IOGEAR's DynaSync provides the EDID support for Windows(R) 7

Package Contents

- 1 MiniView Micro USB PLUS 2 Port KVM Switch
- 1 User Manual
- 1 Quick Start Guide
- 1 Warranty Registration Card

Specifications

Function	GCS632U	Dimensions	GCS632U
CPU Connectors		POP Information	
Monitor	2 x HDB15 Male	10" Peg Hook	4
Audio	2 x stereo speaker	Unit Dimensions	
Keyboard & Mouse	2 x USB Type A	Height	1.00 in. (2.5 cm)
Console Connectors		Depth	2.25 in. (5.7 cm)
Mouse	1 x USB Type A	Width	3.06 in. (7.8 cm.)
Keyboard	1 x USB Type A	Inner Pack	
Monitor	1 x HDB15 Female	Height	9.19 in. (23.3 cm)
Audio	1 x stereo speaker	Length	7.00 in. (17.8 cm)
Cable Length	6 ft. (1.83 m.)	Width	6.44 in. (16.4 cm)
Cable Connections		Inner Pack Qty.	3
Input	USB	Unit Package Dimensions	
Output	USB	Height	8.81 in. (22.4 cm.)
CPU or KVM Connection	USB	Width	6.25 in. (15.9 cm.)
		Depth	2.25 in. (5.7 cm.)
		Master Carton	
		Height	10.13 in. (25.7 cm)
		Width	13.38 in. (34.0 cm)
		Depth	14.75 in. (37.5 cm)
		Master Carton Qty.	12
		Weight	
		Master Carton Wt.	15.05 lbs. (6.83 kg)
		Inner Pack Wt.	3.4 lbs (1.54 kg)
		Unit Pack Wt.	1.05 lbs. (0.48 kg)
		Unit Wt.	0.80 Lbs. (0.36 kg.)