

GHSW8441

## True 4K 4-Port Switcher with HDMI® Connection

- Connect and switch between 4 HDMI® sources on 1 HDMI display
- True 4K resolutions to 4096 x 2160 @ 60Hz (4:4:4)
- Distribute uncompressed audio formats
- Flexible control via push-button, IR remote & RS-232 serial control
- Bi-directional RS-232 support for universal remotes & touch panels



### 4-Port True 4K Switch With HDMI®

The IOGEAR 4-Port True 4K Switch with HDMI connection offers smooth, quick switching between four HDMI video sources such as a computer, Blu-ray or media player, and cable or satellite receivers and a single HDMI display. Send crystal clear, Cinema 4K video reaching true 4K resolutions to 4096 x 2160 @ 60Hz with 4:4:4 Chroma subsampling, High Dynamic Range (HDR) and uncompressed audio for any variety of uses including home theater, in lobbies and conference rooms and for digital signage.


### Flexible Source Switching

Easily switch between each source automatically or manually. Utilize one of three Switch Modes and auto-cycle through your sources with smooth video transitions to display a variety of content. Manually switch between sources with the included IR remote control, or select a source via front panel push-buttons in settings where a remote control is not needed.

- Connect and switch between 4 HDMI® sources to 1 HDMI display
- True 4K resolutions to 4096 x 2160 @ 60Hz (4:4:4)
- Cascade up to 3 levels (64 source ports)
- Distribute uncompressed audio formats
- Flexible control via push-button, IR remote control
- Auto-Switch mode detects & selects new HDMI port connections
- Supports high-speed data rates up to 18 Gbps
- HDCP 2.2 Compliant
- CEC Compliant



Switch between four HDMI video sources such as a computer, Blu-ray or media player, and cable or satellite receivers and a single HDMI display



**Requirements**

- HDMI source
- HDMI Display or projector

**Package Contents**

- 1 x GHSW8441 4-Port 4K Switch with HDMI Connectors
- 1 x Power Adapter
- 1 x IR Remote Control Unit
- 1 x HDMI Cable
- 1 x User Manual
- 1 x Warranty Card

**Specifications**

Function	GHSW8441
<b>Video connections</b>	
Input	HDMI
Output	HDMI
<b>Display Output</b>	
HDMI	HDCP 2.2
<b>Connectors</b>	
RS-232	1 x DB-9 Female
<b>Environment</b>	
Humidity	0-80%
Operation Temperature	32~104°F (0~40°C)
Storage Temperature	-4F ~ 140F (-20 - 60C)
<b>Housing</b>	
Case	Metal
<b>Power Adapter</b>	5V/2A
<b>Power Consumption</b>	5W
<b>Video Resolution</b>	4096 x 2160 @ 60Hz (4:4:4)
<b>Video Streaming</b>	18 Gbps (6Gbps per lane)
<b>Warranty</b>	3 - Years

Dimensions	GHSW8441
<b>Unit Dimensions</b>	
Height	0.98 in
Length	7.87 in
Depth	3.23 in
<b>Unit Package Dimensions</b>	
Height	9.40 in
Length	6.30 in
Depth	2.32 in
<b>Master Carton</b>	
Height	10.04 in
Width	14.89 in
Depth	7.17 in
Master Carton Qty.	6
<b>Weight</b>	
Master Carton Wt.	11.55 lb
<b>Physical Properties</b>	
Unit Weight	1.03 lb
Unit Weight with package	1.83 lb