

PANTONE METALLIC 8402C

PANTONE SOLID 382C

OUTSIDE

Warranty

WE'RE HERE TO HELP YOU! NEED ASSISTANCE SETTING UP THIS PRODUCT?

Make sure you:

1. Use the live chat at www.iogear.com to try and solve any issues you may be having with the product
2. Visit the Tech Info Library/FAQ on www.iogear.com (under the Support tab)
3. Call the 24/7 tech support line at 1-866-946-4327 (U.S. only) or 949-453-8782

Warranty Information

This product carries a 3 Year Limited Warranty. For the terms and conditions of this warranty, please go to <http://www.iogear.com/support/warranty> or call 1-866-946-4327

Register online at <http://www.iogear.com/register>

Important Product Information

Product Model _____

Serial Number _____

Contact

IOGEAR Inc.

Address: 23 Hubble, Irvine, CA 92618 USA

Toll Free: 866-9-IOGEAR

Phone: 949-453-8782

Web site: www.iogear.com

Email: support@iogear.com

About Us



FUN

IOGEAR offers connectivity solutions that are innovative, fun, and stylish, helping people enjoy daily life using our high technology products.

GREEN

IOGEAR is an environmentally conscious company that emphasizes the importance of conserving natural resources. The use of our technology solutions helps reduce electronic waste.

HEALTH

IOGEAR supports healthy and fit lifestyles. By integrating products with the latest scientific developments, IOGEAR's solutions enhance the life of end-users.

© 2008 IOGEAR, INC.

IOGEAR

Quick Start Guide

DVI-D CAT5e/6 MiniExtender

QVE200
PART NO. Q1049

INSIDE

Package Content

- 2 x HDMI Extender (1 Local & 1 Remote)
- 1 x Quick Start Guide
- 1 x Warranty Card

System Requirement

- PC source with DVI-D connection
- Display device with Single Link DVI-D connection
- A Solid CAT5e/6 cable

Note: Extension range may vary with different devices or CAT5e/6 cables

Overview

Start Here!

1. DVI-D Connection
2. Signal LED

3. CAT5e/6 Port
4. Power LED



Installation

Note: Please make sure your PC source and display unit are powered off before you start.

STEP 1

Plug one of the MiniExtender into the DVI port of your PC source. Lock the MiniExtender by turning the two knobs clockwise.



STEP 2

Plug the other MiniExtender into the DVI port of your display. Lock the MiniExtender by turning the two knobs clockwise.



Installation

STEP 3

Plug in the CAT5e/6 cable to the MiniExtenders from the PC source and display. Make sure the connection is not loose.



FINAL STEP

Turn on your computer and display unit.