



PANTONE METALLIC 8402C



PANTONE SOLID 382C

OUTSIDE

Warranty

WE'RE HERE TO HELP YOU! NEED ASSISTANCE SETTING UP THIS PRODUCT?

Make sure you:

1. Use the live chat at www.iogear.com to try and solve any issues you may be having with the product
2. Visit the Tech Info Library/FAQ on www.iogear.com (under the Support tab)
3. Call the 24/7 tech support line at 1-866-946-4327 (U.S. only) or 949-453-8782

Warranty Information

This product carries a 3 Year Limited Warranty. For the terms and conditions of this warranty, please go to <http://www.iogear.com/support/warranty> or call 1-866-946-4327

Register online at <http://www.iogear.com/register>

Important Product Information

Product Model _____
Serial Number _____

Contact

IOGEAR Inc.

Address: 23 Hubble, Irvine, CA 92618 USA
Toll Free: 866-9-IOGEAR
Phone: 949-453-8782
Web site: www.iogear.com
Email: support@iogear.com

About Us



FUN

IOGEAR offers connectivity solutions that are innovative, fun, and stylish, helping people enjoy daily life using our high technology products.

GREEN

IOGEAR is an environmentally conscious company that emphasizes the importance of conserving natural resources. The use of our technology solutions helps reduce electronic waste.

HEALTH

IOGEAR supports healthy and fit lifestyles. By integrating products with the latest scientific developments, IOGEAR's solutions enhance the life of end-users.

© 2008 IOGEAR, INC.



Quick Start Guide

2-Port HDMI Audio/Video Splitter

GVS182
PART NO. Q1077

INSIDE

Package Contents

- 1 x 2-Port HDMI Audio/Video Splitter
- 1 x Power Adapter
- 1 x Quick Start Guide
- 1 x Warranty Card


Requirements

- HD TVs or displays with HDMI input connections
- Digital media source device with a HDMI output connection

Overview

Start Here!

1. Port 1 LED
2. Port 2 LED
3. Power LED
4. Reset Button



5. Power Adapter Port
6. Input Port
7. Output Port 2
8. Output Port 1



Installation

STEP 1

Please make sure your HD TVs or displays and HD media source are powered off before you start.

STEP 2

Connect the power adapter to the power outlet and the HDMI splitter's power adapter port.



STEP 3

Connect a HDMI cable to the output port from the HD media source and the input port from HDMI splitter.



Installation

STEP 4

Connect HDMI cables to the input ports of your HD TVs or displays and the output ports of the HDMI splitter.



FINAL STEP

You can now turn on your HD media source and your HD TVs or displays.

Reset Button

After hot swapping any HDMI device from the HDMI Splitter, please press the reset button once so that it can re-adjust the video resolution to fit your HD TVs or displays.